



The 608 D/DF series lock is the typical armoured door lock with a double-bit key.

The key operates the bolts and slides, and retracts the latch.
The handle retracts the latch

- Locks configured with the latch at the top or bottom
- Locks with latch and bolt or bolt only

(maximum) with the added RBS bolt reinforcement system (option H)

Gost certification for the Russian market 

IMP certification for the Polish market 

Case sizes 63, 73 and 89 mm.
Key – handle centre distance 85 mm.
8 mm square handle spindle.
Piston bolt centre distances
28, 37/38 mm.
Rim version bolt
protrusion 3.5/13.5 mm.
Mortise version bolt
protrusion 0.5 mm.
Reversible latch, diameter
20 mm, protrusion 18/28 mm.
Bolt diam.18 mm, stroke 40 mm, 4 turns
of the key.
Three-point closure, rod stroke 20 mm
Long 110 mm key included,
optional 95 mm key also available.

- All the 608 D/DF double-bit locks can be re-keyed upon request, meaning that the service and/or master keys can be replaced with new keys that exclude the former, in order to ensure greater security and privacy. This incredibly quick and simple operation can be performed directly by the user in just a few seconds with the door open, with no need to replace the interior parts of the lock, or to disassemble the panels, escutcheons, or anything else. The locks can be re-keyed up to 3 times. The keys have plastic covers in different colours, and are always enclosed within opaque heat-sealed bags:
- The master keys have a grey/violet/blue cover for each re-keying operation
 - The service keys (2 turns and latch) always have a red plastic cover
 - The service keys (half turn, latch only) do not have covers.

600 D/DF Datasheet ENG 2017_03 - Non-contractual document. Subject to change.